

Voice Alarm

Contact Interface Module (CIM)

The Contact Interface Module (CIM) serves as an interface module for the Honeywell Voice Alarm system. The CIM provides 8 control contacts – four of these can be monitored for short and open circuit faults.



583341.21 Contact Interface Module (CIM)

The CIM is connected to the DOM module of the Honeywell system via the TWI databus.

Each of the 8 contacts can be configured as either inputs or outputs enabling the system to be controlled externally and to provide system status information and cause and effect control/management.

Key Features:

- Enables third party systems to interface with the Honeywell voice alarm system
- 8 freely programmable contacts as inputs or outputs
- Up to 4 contacts can be monitored
- Two-Wire Interface (TWI) to DOM
- EN 54-16 approved
- CPD No. 0786-CPD-20997

Voice Alarm

583341.21 Contact Interface Module (CIM)

Technical Specifications

SPECIFICATION	
DIMENSIONS	
Height, Width, Depth	105 mm, 40mm, 105mm
Weight	Approx 0.31kg
HOUSING COLOR	
Body	Grey, similar to RAL 7016
MONITORING CONTACTS / INPUTS	
Contact load max	+36 V / 50mA
ENVIRONMENTAL SPECIFICATIONS	
Ambient temperature	-5°C to +55°C
Humidity	15 % to 90 %

DESCRIPTION	ORDER CODES
D1 Contact Interface Module (CIM)	583341.21

Honeywell Life Safety Systems

Tel: +44 (0) 116 246 2000
Fax: +44 (0) 116 246 2300
Email: ukorders@honeywell.com
140 Waterside Road
Hamilton Industrial Park
Leicester
LE5 1TN

May 2013
© 2013 Honeywell International Inc.

Honeywell